

Firing Cable

Art.-No.: 1100012



Features

Cable

- 2 x 0.75 mm² twisted, colour black and brown, cable resistance not more than 26 Ohms/km
- Fulfills UK DEF STAN 61-12 part 17
- NSN 6145-99-017-3378

Drum

- High quality cable drum with crank handle and break, colour orange/black
- Connectors mounted on front plate

Technical Data

Cable Length	Loop Resistance (approx.)	Dimensions L x H x D	Weight app.	Article No.
200 m	11 Ohms	31 x 36 x 22 cm	7.4 kg	1100012-20
250 m	14 Ohms	31 x 36 x 22 cm	8.4 kg	1100012-25
500 m	28 Ohms	39 x 45 x 22 cm	15.5 kg	1100012-50



Firing Cable

Art.-No.: 1100012

Specifications

Cable cross section	2 x 0.75 mm ²
Overall diameter	4.9 mm
Single core diameter	2.45 mm
Conductor diameter	approx. 1.1 mm
Conductor material	24 x 0.193 stranded bare copper class 5
Insulation wall thickness	> 0.6 mm
Insulation material	PVC TI2 black and brown, 90 +/-2 ShA
Twisting	twisted to open pair
Lay length	approx. 35 mm
Weight nom	20 kg/km net
Conductor resistance	max 26 Ω/km @ 20°C
Ignition voltage	1.5 kV
Test voltage	2.5 kV
Reference standard	DEF STAN 61-12 part 17
NATO Stock Number	6145-99-017-3378